

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
29 March 2001 (29.03.2001)

PCT

(10) International Publication Number  
WO 01/21115 A1

(51) International Patent Classification<sup>7</sup>: A61F 5/44

(21) International Application Number: PCT/DK00/00478

(22) International Filing Date:  
1 September 2000 (01.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PA 1999 01319 17 September 1999 (17.09.1999) DK

(71) Applicant (for all designated States except US): COLO-  
PLAST A/S [DK/DK]; Høltedam 1, DK-3050 Humlebaek  
(DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CIOK, Danuta

[PL/DK]; Violens Kvarter 8, DK-2990 Nivå (DK). VON  
BÜLOW, Martin [DK/DK]; Fredensvej 9B, DK-3060  
Espergærde (DK).


(74) Agents: CARLSSON, Eva et al.; Internationalt Patent-  
Bureau, Høje Taastrup Boulevard 23, DK-2630 Taastrup  
(DK).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT  
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility  
model), DK, DK (utility model), DM, DZ, EE, EE (utility  
model), ES, FI, FI (utility model), GB, GD, GE, GH, GM,  
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,  
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,  
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK  
(utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ,  
VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian

[Continued on next page]

(54) Title: A COLLECTING BAG HAVING AN ACCOMMODATING MEANS FOR A CLOSURE DEVICE



(57) Abstract: The collecting bag comprises a bag member (1) formed by two film blanks (2, 3) with joined edges, and a discharge portion (6) comprising a discharge opening. A closure device (7) at the discharge portion (6) for bringing the bag from a discharge position, in which the bag is open, to a position of use, in which the bag is closed, is accommodated in accommodating means (8) in the position of use of the bag. The accommodating means (8) comprises at least one open receptacle formed in said bag member (1) and has a basis portion (9) in which said film blanks (2, 3) are undetachably connected to each other. The accommodating means may comprise a retaining element in the form of a strip (10) having at least one engagement section for releasable engagement with a corresponding section or corresponding sections on said bag member (1) or on the opposite end of said retaining element.

WO 01/21115 A1



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *With international search report.*

A collecting bag having an accommodating means for a closure device.

5       The present invention relates to a collecting bag for human body wastes comprising a bag member formed by two film blanks with joined edges defining the outer contours of the bag member, an inlet opening provided in one of said film blanks, connecting elements  
10 surrounding said inlet opening for connection of the bag to a body orifice, a discharge portion at a distance from the inlet opening comprising a discharge opening, a closure device at the discharge portion for bringing the bag from a discharge position, in which  
15 the bag is open, to a position of use, in which the bag is closed, and accommodating means for accommodating said closure device in the position of use of the bag.

In such collecting bags the discharge portion is normally temporarily attached to the bag member in the  
20 position of use of the bag in order to attain a compact appearance in this position and to prevent the discharge portion and the closure device from dangling which might be uncomfortable to the user. In bags having an elongated, substantially flat discharge  
25 portion, this portion is folded or rolled up in the direction of the bag member, partly in order to close the bag and partly to attain said compact appearance and the attachment to the bag member.

WO96/19164 discloses a collecting bag of this kind  
30 in which the discharge portion is rolled up on a clip fastened to one of the film blanks.

GB patent applications Nos. 2 268 065 and 2 000 683 disclose collecting bags, in which strips of the interlocking-elements type, such as Velcro, are placed  
35 on each of the film blanks of the discharge portion and

which after rolling or folding the discharge portion tightly are brought into contact with each other.

In EP patent application No. 13 109 the folded discharge portion is tucked into a gap provided between  
5 a strip fixed to one wall of the bag and the wall itself.

In all of the above documents it is a prerequisite that the discharge portion is substantially flat. In collecting bags having a closure device of some extent,  
10 eg. a valve or a clamp, these solutions may not be applied.

US patent No. 2,520,831 discloses a collecting bag in which the folded discharge portion, which is closed by means of a clamp, is accommodated in a pouch  
15 provided at the proximal end of the discharge portion in the position of use of the bag, in which the pouch is closed by means of a zipper-like slide fastener. Due to the structure of the elements of the closure device, opening and closing of the bag require some dexterity,  
20 eg. the discharge portion has to be held manually within the pouch when activating the slide fastener and has to be withdrawn from the pouch in order to empty the bag. In addition, the use of a slide fastener renders the manufacture of the collecting bag expensive  
25 and cumbersome.

US patent No. 4,519,797 discloses a cover for an ostomy pouch having a drain fitting at the bottom of the pouch. The cover has an opening allowing the pouch to be mounted in the usual manner on the plate worn by  
30 the patient. The cover has an integral pocket which receives the drain fitting to prevent irritation to the sensitive portions of the anatomy.

This solution, however, while preventing the drain fitting from directly contacting sensitive portions of  
35 the anatomy, contributes to the bulkiness of the pouch,

thereby compromising the demand for discretion.

US patent No. 4,449,971 discloses a collecting bag of the initially stated kind, in which the accommodating means in the form of a pocket having an entrance slit is formed on an extension of the bag member. Similar arrangements are shown in e.g. US patents Nos 3,865,165 and 4,306,029.

The object of the present invention is to improve a collecting bag of the kind mentioned in the introduction with respect to ease of operation and manufacturing conditions and which furthermore may be used regardless of the type of closure device, at the same time improving both the comfort and the discretion.

For achieving this, a collecting bag according to the invention is characterized in that said accommodating means comprises at least one open receptacle formed in said bag member within said outer contours and has a basis portion in which said film blanks are undetachably connected to each other, and that the periphery of the basis portion is situated at a distance from the joined edges of the bag member and the discharge portion.

By the provision of an accommodating means in the form of an open receptacle having a basis portion, it is very simple to place the closure device in the accommodating means. The position of the basis portion entails that the outer contours of the bag member are not affected by the accommodating means, and at the same time, a free passage is provided from the bag member to the discharge portion. The undetachable connection between the film blanks makes it possible to lodge the closure device in its entirety in the accommodating means so that it does not protrude outside the arched planes formed by the film blanks

when the bag is expanded by the contents. Furthermore, the accommodating means may be formed in an easy and inexpensive manner thus reducing the manufacturing and material costs.

5 In the following the invention will be described in further detail with reference to the schematic drawings, in which the bag is shown in the shape it will assume when at least partly filled and

Fig. 1 shows a side view of a collecting bag  
10 according to the invention in a discharge position;

Fig. 2 shows a plan view of the collecting bag shown in Fig. 1;

Fig. 3 shows a plan view of the collecting bag in a position of use;

15 Fig. 4 shows a cross-sectional view of the collecting bag along the line IV-IV in Fig. 3;

Fig. 5 shows a side view of the collecting bag in the position shown in Fig. 3; and

Fig. 6 shows a longitudinal section of the  
20 collecting bag along the line VI-VI in Fig. 3.

The collecting bag shown in the drawings comprises a bag member 1 formed by two film blanks 2,3 which are joined along their edges by means of a seam 4 made by welding or in any other convenient manner and defining  
25 the outer contours of the bag member. The film blanks may be made from any suitable flexible plastic sheet or foil material.

In the film blank 3 which in use is intended to face the user and thus forms the back wall of the bag,  
30 an inlet opening, not shown, is provided which in a manner known *per se* is surrounded by connecting elements 5 for connection of the bag to a body orifice in the form of a so-called stoma in the user's abdominal wall.

35 At a distance from the inlet opening and the

connecting elements 5, the bag is designed with a discharge portion 6 having a discharge opening, not shown in detail, through which the bag may be emptied of its contents.

5 In order to bring the bag from the open or discharge position shown in Figs. 1 and 2 to a position of use, in which the bag is closed, the collecting bag comprises a closure device 7 which in the embodiment shown is designed as a valve but which as well be  
10 designed in any other way.

An accommodating means 8 for accommodating the closure device 7 in the position of use of the collecting bag is designed in the bag member 1. The accommodating means comprises an open receptacle with  
15 a basis portion 9 surrounded by portions 2a of the front film blank 2. In the basis portion 9 the two film blanks 2,3 are, as most clearly seen in Figs. 4 and 6, connected to each other in an undetachable manner, eg. by means of a welded or heat-sealed joint extending  
20 along the periphery 9a of the basis portion 9 or by gluing the film blanks together in this area. As seen in Figs. 3 to 6 the closure device 7 is accommodated in the accommodating means 8 in its entirety and does not protrude outside the outer contours of the bag in the  
25 plane of the bag, neither does it protrude outside the arched plane defined by the remaining portions 2b of the front film blank. Thus, a very compact appearance of the bag is obtained in the position of use.

It is of course conceivable, although not  
30 preferred, to place the closure device in the corresponding receptacle formed at the back of the bag member.

In order to improve the securing of the closure device 7 in the open receptacle formed by the basis  
35 portion 9 and the portions 2a of front film blank 2

surrounding the basis portion 9, the accommodating means may further comprise a retaining means, which in the embodiment shown is provided in the shape of a strip 10 which in one end is undetachably connected to the bag member and in the other end has an engagement section for releasable engagement with a corresponding section on the bag member. The engagement sections may comprise interlocking elements, eg. of the Velcro type. The strip 10 may also be undetachably secured in a middle section and have foldable ends with corresponding engagement sections, said foldable ends having lengths enabling them to reach around the closure device 7 for engagement or it may be provided separately and comprise an engagement section in each end.

Other types of retaining means may be conceivable, eg. it is possible to provide the closure device itself with an engagement section for releasable engagement with a corresponding section in the basis portion.

The periphery 9a of the basis portion 9 is situated at a distance from the joined edges of the bag member, ie. the seam 4, and the discharge portion 6 in order to permit the contents of the bag to flow out of the discharge portion 6 and the discharge opening during emptying of the bag. It is of course possible to place the accommodating means in the vicinity of one of the edges as long as there is still a free passage between the bag member and the discharge portion.

The basis portion 9 of the accommodating means has cross-sectional dimensions corresponding to the dimensions of the closure device 7. By this design, a safe retention of the closure device in the accommodating means 8 is obtained and at the same time the volume available for body wastes in the remaining part of the bag is reduced as little as possible.



The invention should not be regarded as being limited to the embodiment described in the above but various modifications may be carried out without departing from the scope of the following claims.

- 5       For example, although the invention has been described only with reference to one kind of closure device, viz. a valve, it is of course possible to apply it to other forms of closure devices comprising eg. clamps or adhesive connections.

## P A T E N T C L A I M S

1. A collecting bag for human body wastes comprising:

a bag member (1) formed by two film blanks (2,3)  
5 with joined edges defining the outer contours of the bag member,

an inlet opening provided in one of said film blanks (3),

connecting elements (5) surrounding said inlet  
10 opening for connection of the bag to a body orifice,

a discharge portion (6) at a distance from the inlet opening comprising a discharge opening,

a closure device (7) at the discharge portion (6) for bringing the bag from a discharge position, in  
15 which the bag is open, to a position of use, in which the bag is closed, and

accommodating means (8) for accommodating said closure device (7) in the position of use of the bag,

c h a r a c t e r i z e d i n t h a t

20 said accommodating means (8) comprises at least one open receptacle formed in said bag member (1) within said outer contours and has a basis portion (9) in which said film blanks (2,3) are undetachably connected to each other, and that the periphery (9a) of  
25 the basis portion (9) is situated at a distance from the joined edges (4) of the bag member (1) and the discharge portion (6).

2. A collecting bag according to claim 1, c h a r a c t e r i z e d i n t h a t said film blanks  
30 (2,3) are connected to each other by means of a heat-sealed joint extending along the periphery (9a) of the basis portion (9).

3. A collecting bag according to claim 1, c h a r a c t e r i z e d i n t h a t said film blanks  
35 (2,3) are connected to each other by gluing.

4. A collecting bag according to any of claims 1 to 3, c h a r a c t e r i z e d in that said accommodating means (8) comprises a retaining means (10) for holding the closure means (7) in said open 5 receptacle in the position of use of the bag.

5. A collecting bag according to claim 4, c h a r a c t e r i z e d in that said retaining means comprises a strip (10) having at least one engagement section for releasable engagement with a corresponding 10 section or corresponding sections on said bag member (1) or on the opposite end of said retaining means.

6. A collecting bag according to any claims 1 to 5, c h a r a c t e r i z e d in that said basis portion (9) has cross-sectional dimensions 15 corresponding to the dimensions of the closure device (7).

1/4




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK 00/00478

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F5/44

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No. |
|------------|---|-----------------------|
| Y          | US 4 449 971 A (CAWOOD CHARLES D)<br>22 May 1984 (1984-05-22)<br>cited in the application<br>column 4, line 4 - line 41; figures<br>---     | 1-6                   |
| Y          | US 3 650 272 A (ERICSON RICHARD E)<br>21 March 1972 (1972-03-21)<br>column 2, line 11 - line 27; figures 3,9<br>---                         | 1-6                   |
| A          | US 3 865 165 A (GLASS DANIEL S)<br>11 February 1975 (1975-02-11)<br>cited in the application<br>column 2, line 36 - line 62; figures<br>--- | 1-4                   |
| A          | EP 0 185 809 A (MANFREDI FRANK ANTHONY)<br>2 July 1986 (1986-07-02)<br>figure 1<br>---<br>-/-   | 5                     |

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

1 December 2000

Date of mailing of the international search report

11/12/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Sánchez y Sánchez, J



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/DK 00/00478

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages                       | Relevant to claim No. |
|------------|--|-----------------------|
| A          | US 4 306 029 A (CARPENTER DAVID F)<br>15 December 1981 (1981-12-15)<br>cited in the application<br>----- |                       |

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/DK 00/00478

| Patent document<br>cited in search report |   | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|---|---|---------------------|----------------------------|---------------------|
| US 4449971                                | A | 22-05-1984          | NONE                       |                     |
| US 3650272                                | A | 21-03-1972          | NONE                       |                     |
| US 3865165                                | A | 11-02-1975          | NONE                       |                     |
| EP 0185809                                | A | 02-07-1986          | NONE                       |                     |
| US 4306029                                | A | 15-12-1981          | NONE                       |                     |